

SATELLITE MULTISWITCHES

MODEL:SH13138E

DESCRIPTION:13x13x8 Satellite Multiswitch



Features:

- 12 satellite IF and 1 terrestrial TV inputs for 8 satellite receiver
- 12 satellite IF inputs selected by 13V、18V、22KHz and DisEqC 2.0 signal
- Low insertion loss, high isolation and return loss
- SAT-IF-PATHs to the subscribers are active and supplied by the receiver
- Sheet metal housing with plastic holder
- Design good for indoor usage

Specifications

Specifications		Typical	QC Limit	Remark
Item				
Frequency Range		Terr.:47~862MHz SAT:950~2150MHz		
Inputs		12 SAT+1 Terr.		F connectors
Outputs		8 Receiver		F connectors
Thru Loss	Terr.	3dB	4dB	
	SAT	3dB	4dB	
TAP Loss	Terr.	6dB	8dB	
	SAT	1dB	3dB	
Return Loss	Terr.	12dB	10dB	
	SAT	12dB	10dB	
Stop band attenuation	Terr.	28dB	25dB	
	SAT	28dB	25dB	
Isolation	H/V	30dB	25dB	
	REC-REC	30dB	25dB	
Power Adapter		IN:100~240V OUT:18V 2000mA		
Dimensions (L,W,H)		298x136x42		mm